

CAPPLUS

TECHNOLOGIES

CPT T200

Automatic Powder Transfer



FEATURES INCLUDE:

- HIGHLY POLISHED 304SS POWDER HOPPER
FILTER WITH AUTOMATIC CLEANING SYSTEM
PROXIMITY LEVEL DETECTOR
DISCHARGE VALVE
APPROXIMATE .75CF CAPACITY
- SS CONTROL PANEL - WALL MOUNT TYPE:
VENTURI TO CONVERT AIR VACUUM
ON/OFF CONTROLS
AIR FILTER, REGULATOR, GAUGE
ADJUSTABLE FEED AND CLEANING CYCLES
FLEXIBLE AIRLINE TUBING
- MATERIAL HANDLING ITEMS:
PRODUCT CONTAINER VACUUM WAND
ANTI-STATIC FLEXIBLE HOSE
LONG SLOPING 90 DEG. SS TUBE
- **OPTIONAL T200P SYSTEM** (MOUNTED ON PLATFORM WITH CASTORS)
- HIGHLY POLISHED 304SS POWDER HOPPER:
FILTER WITH AUTOMATIC CLEANING SYSTEM
PROXIMITY LEVEL DETECTOR
DISCHARGE VALVE
APPROXIMATE .75CF CAPACITY
- SS CONTROL PANEL
VENTURI TO CONVERT AIR VACUUM
ON/OFF CONTROLS
AIR FILTER, REGULATOR, GAUGE
ADJUSTABLE FEED AND CLEANING CYCLES
FLEXIBLE AIRLINE TUBING
- MATERIAL HANDLING ITEMS:
PRODUCT CONTAINER VACUUM WAND
ANTI-STATIC FLEXIBLE HOSE
LONG SLOPING 90 DEG. SS TUBE

SPECIFICATIONS:

FEEDING CAPACITY (T200)	50 TO 200 KG/HOUR
CONSTRUCTION	304SS #200 FINISH
DIAMETER OF VACUUM HOSE	32MM
DIAMETER OF AIR LINES	12MM
AIR CONSUMPTION	1.3M ² /MIN 4KG /CM ²
AIR SUPPLY REQUIREMENTS	50L/MIN 6KG/CM ²
POWER REQUIREMENTS	110V/1PH/60HZ