

CAPPLUS

TECHNOLOGIES

CPT Ultra

Automatic Rotary Tablet Press



FEATURES INCLUDE:

- RATED AT 28,500 TO 91,200 TABLETS PER HOUR
- 6 TONS MAXIMUM MAIN COMPRESSION
- 13MM ROUND OR 14MM SHAPED MAIMUM TABLET DIAMETER/LENGTH
- 8.5MM MAXIMUM TABLET THICKNESS
- .5MM TO 16MM MAXIMUM FILLING DEPTH
- 1 TO 6MM PUNCH INSERTION DEPTH
- CHANGE RAIL WITH QUICK RELEASE CLAMPS
- PRODUCT HOPPER WITH BUTTERFLY VALVE
- LOWER SS ENCLOSURES
- SPRING BUFFER SYSTEM
- PUNCH RESTRAINER SYSTEM
- UPPER PLEXIGLAS ENCLOSURES WITH SAFETY LOCKS
- DUST COLLECTION PORT
- AUTO LUBRICATION SYSTEM FOR BOTH UPPER AND LOWER PUNCHES
- 5HP MAIN DRIVE MOTOR
- STANDARD ELECTRICAL - EMERGENCY STOP, INCH, VARIABLE SPEED CONTROLS, ALARM, COUNTER AND SPEED INDICATORS
- HAND DIAL ADJUSTMENTS FOR FILLING DEPTH, PENETRATION DEPTH AND TABLET THICKNESS

SPECIFICATIONS:

STATIONS	19
TABLETS PER HOUR	28,500 - 91,200
REVOLUTION OF DIE TABLE	25 TO 80RPM
MAXIMUM TABLET DIAMETER	13MM ROUND
MAXIMUM FILLING DEPTH	.5 TO 16MM
UPPER PUNCH PENETRATION	1 TO 6MM
WEIGHT OF MACHINE	1800KG
DIMENSIONS	750MM x 750MM x 1860MM
ELECTRICAL	220V/3PH/60HZ



ULTRA FEED FRAME



WEIGHT AND LOWER PRE-COMPRESSION