

CAPPLUS

TECHNOLOGIES

1 CF PORTABLE V-BLENDER WITH CANTILEVER DESIGN



AVAILABLE IN 16 QT. TO 2 CF

FEATURES

- CANTILEVER DESIGN FOR INTERCHANGEABLE SHELLS
- RATED FOR UP TO 60LBS PER CUBIC FOOT
- ACCESS OPENINGS 10" INCHES IN DIAMETER
- 24 RPM SHELL SPEED
- 4" HEAVY DUTY LOCKING CASTERS
- 304SS 1.5" SQUARE TUBING FRAME
- #4 FINISH (SATIN FINISH) ON EXTERIOR OF MACHINE
- HINGED SAFETY ENCLOSURE WITH POLYCARBONATE WINDOW
- 16QT. 1 AND 2 CF CAPACITIES AVAILABLE

SPECIFICATIONS

WIDTH: 52"
HEIGHT: 51"
LENGTH: 43"
WEIGHT: 167 LBS.
DISCHARGE CLEARANCE: 15"

ELECTRICAL

POWER REQUIREMENTS: 1 PH / 110V / 60HZ
MOTOR .5 OR 1 HP AVAILABLE

OPTIONAL EQUIPMENT:

DIGITAL RPM
TIMER 0-15 MINUTES WITH AUTOMATIC SHUT OFF



OVERHEAD VIEW



BOTTOM VIEW



CONTROL PANEL

CAPPLUS TECHNOLOGIES



CLOSE UP VIEW OF
SHELL MOUNTED ON FRAME



NEW 2" ROBUST
FRAME DESIGN



INTENSIFIER BAR WITH
.75HP / 1725RPM DRIVE SYSTEM

INTENSIFIER BAR
MOUNTED IN
V-BLENDER



6 SHELL SIZES		MAX. POWDER WT/SHELL	
DRY QUARTS	CUBIC FEET	LBS.	KG
16	0.62	37.2	16.87
26	1	60	27.22
32	1.24	74.4	33.75
52	2	120	54.43