CAPPLUS Technologies

CPT COLOR MIXER

10	100.000
	and the second se
	THE AT
	1
Ν.,	100 ·
	ALC: NO.
	2.2.5
	I IIIII
- 12	
	G *
	- Jones
	A COLOR
-	

FEATURES	BENEFITS
A SPECIFICALLY DESIGNED IMPELLER IS INSTALLED AT THE BOTTOM OF THE DRIVE SHAFT AND INSIDE A CIRCULAR COWLING	INSURES A HOMOGENOUS BLEND
MAXIMUM IMPELLER MIXING SPEED OF 1500 RPM	ALLOWS DISPERSING, MIXING, HOMOGENIZING AND EMULSIFYING WHILE VACUUM REMOVES AIR WITHIN PRODUCT
THE MACHINE IS DESIGNED TO BE FLOOR ANCHORED AND WALL MOUNTED	TAKES UP VERY LITTLE FLOOR SPACE
USING A COMPRESSED AIR DRIVEN CYLINDER	THE MIXING HEAD MOVES EFFORT LESSLY UP AND DOWN TO THE DESIRED POSITION WHEN A GEL TRANSFER TANK IS MOVED INTO POSITION

SPECIFICATIONS

ROTATION SPEED	
OF IMPELLER	MAX 1,500 RPM
Main motor	10HP
VACUUM PUMP	ЗНР
Power	220V / 3PH AC
	Frequency: 60Hz
	CONSUMPTION: MAX 8KW
Air	5-7 Кс/См2
DIMENSIONS	1,000W x 1,100D x 2,500H (мм)
ESTIMATED WEIGHT	450KG