

CAPPLUS TECHNOLOGIES

CPT-225 TOP & BOTTOM LABELER

FLEXIBLE LABEL HEAD TILTS ON X-Y AXIS
FOR FLAT, TAPERED AND SHAPED CONTAINERS

ADVANTAGES

- MORE CONTAINER SHAPES
- TALLER AND WIDER CONTAINERS
- 360 DEGREE TOUCH SCREEN
- SELF TEACHING SENSORS
- ENCLOSED SLIDE OUT CONTROLS

SPECIFICATIONS:

• RANGE OF LABEL SIZE	6-170MM (1/4 - 6.7") (H) 6-300MM (1/4 - 11.8") (W)
• RANGE OF CONTAINER WIDTH	6.5MM - 203MM (0.26" - 8")
• RANGE OF CONTAINER HEIGHT	FLAT - 203MM (0" - 8")
• CONVEYOR WIDTH	160MM (6.3")
• POWER SOURCE	110/220 V 50/60 Hz 1 PH
• POWER CONSUMPTION	0.880 kW
• LABEL DISPENSING SPEED	40M/MIN (131.2'/MIN)
• CONVEYOR SPEED	40M/MIN (131.2'/MIN)
• LABEL SPOOL DIAMETER	356MM (14")
• LABEL SPOOL INNER CORE	76MM (3")
• DRIVE MOTOR	STEPPER
• PLC	PANASONIC
• DIMENSIONS (L-W-H)	1,835 x 800 x 1,360MM 72.2" x 31.5" x 53.5"



FEATURES	BENEFITS
CPT-225'S TWO-SIDE APPLY DESIGN APPLIES LABELS TO TOP AND BOTTOM OF PRODUCT IN ONE PASS	
MANUAL ADJUSTMENTS	
ADJUSTABLE APPLICATOR HEIGHT	SUITABLE FOR A WIDE VARIETY OF CONTAINERS AND LABELS
ADJUSTABLE CONVEYOR HEIGHT	EASY TO ADAPT TO ANY EXISTING PACKAGING LINE
MANUAL POSITION SETTING	EASY TO USE ADJUSTMENTS ENSURE LABELS ARE PLACED ACCURATELY ON THE CONTAINER
TOUCH SCREEN CONTROLS	
5.5" COLOR LCD TOUCH SCREEN CONTROLS	EASIER OPERATION OF CONTROLS
TOUCH SCREEN ROTATES 360 DEGREES	ALLOWS THE MACHINE TO BE CONTROLLED FROM ANY POSITION
STORES UP TO 30 PRODUCT SETTINGS	FASTER AND MORE ACCURATE SETUP
BUILT-IN OPERATING INSTRUCTIONS	ENABLES QUICK SETUP AND EASY CHANGEOVER
EASY TO FOLLOW FAULT INSTRUCTIONS	ENABLES OPERATOR TO QUICKLY IDENTIFY AND FIX PROBLEMS
SCREENSAVER	REDUCES THE RISK OF SCREEN BURN
DATA STORAGE FOR MAINTENANCE AND USAGE	SIMPLIFIES SCHEDULING OF MAINTENANCE ACTIVITIES
BUILT-IN PRINTER CONTROLS	ALLOWS FOR 'PLUG & PLAY' FUTURE PRINTER UPGRADES

CAPPLUS

TECHNOLOGIES

FEATURES	BENEFITS
SENSOR FEATURES	
PRODUCTION PRESET - STOP FUNCTION	AUTOMATICALLY STOPS ONCE THE PRE-SET QUANTITY HAS BEEN MET
MISSING LABEL AUTO STOP SYSTEM	ENSURES ALL PRODUCTS ARE LABELED
LABEL COUNTDOWN	ALLOWS OPERATOR TO MONITOR RUN PROGRESS
BATCH COUNTER	EASY TO KEEP TRACK OF BATCHES
LABEL COUNTER	SIMPLIFIES REGULATORY TRACKING OF LABELS
CONTAINER/PRODUCTION RUN COUNTER	PROVIDES TOTAL PRODUCTION QUANTITY
LABEL POSITION SET	ENSURES LABEL PLACED CORRECTLY ON PRODUCT
ONE TOUCH LABEL SENSOR	ALLOWS OPERATOR TO USE "ONE TOUCH" FEATURE ON SENSOR TO TEACH THE SENSOR THE LABEL CHARACTERISTICS
AUTO LABEL SENSOR SET	DETECTS LABELS AND SETUP MACHINE AUTOMATICALLY FROM TOUCH SCREEN
AUTO LABEL LENGTH SET	DETECTS LABEL LENGTHS AND SETUP MACHINE AUTOMATICALLY FROM TOUCH SCREEN
DESIGN AND CONSTRUCTION	
ADJUSTABLE TO 8 SPEEDS	EASILY ADJUSTS TO LINE SPEEDS
BATTERY FREE MICROPROCESSOR	MAINTAINS DEFAULT SETTINGS AND MEMORY EVEN AFTER SITTING IDLE FOR LONG PERIODS
SLIDE-OUT CONTROLS AND ELECTRONICS STORED IN LOWER CABINETS	ENABLES QUICK AND EASY SERVICING
MANUFACTURED WITH STAINLESS STEEL AND ANODIZED ALUMINUM	ROBUST, LONG LASTING CONSTRUCTION WITH QUICK AND EASY CLEANUP
MANUFACTURED TO STRICT ISO 9001 STANDARDS	HIGH QUALITY, CONSISTENT MANUFACTURING ENSURES EASY REPAIRS AND/OR UPGRADES
GMP COMPLIANT	DESIGNED TO EASILY SURPASS STANDARDS OF COMPLIANCE AUDITORS
FULLY SYNCHRONIZED CONTROLS	ENSURES ALL COMPONENTS RUN AND THE PROPER SPEED
STEPPER DRIVEN MECHANISM	FINE ADJUSTMENT ALLOWS PRECISE LABEL PLACEMENT

NOT QUITE RIGHT FOR YOU? ADD A PRINTER, UPGRADED SENSOR OR WRAP STATION. OUR MACHINES ARE ENGINEERED FOR EASY MODIFICATION. GIVE US A CALL TO DISCUSS YOUR PARTICULAR NEEDS.